

SECTION I SECTION II	Material Identity Manufacturer's Information
SECTION III SECTION IV	Physical/Chemical Characteristics Fire and Explosion Hazard Data
SECTION V	Reactivity Data
SECTION VI	Health Hazard Data
SECTION VII	Precautions for Safe Handling and Use

SECTION VIII
SECTION IX
SECTION X
SECTION XI
SECTION XII

Control Measures Label Data Transportation Data Site Specific/Reporting Information Ingredients/Identity Information

SECTION I - Material Identity

Part Number/Trade Name	Graphite Adhesive
National Stock Number	n/a
CAGE Code	n/a
Part Number Indicator	n/a
MSDS Number	2628
HAZ Code	В

SECTION II - Manufacturer's Information

Manufacturer Name Street Address 2 Address 3 Country Post Code Emergency Phone Information Phone Coidan Graphite Products Ltd Station Road Kirk Hammerton YORK UK YO26 8DQ (01423) 330492 (01423) 330492

MSDS Preparer's Information

Date MSDS Prepared/Revised	MAY 2011
Active Indicator	n/a

SECTION III - Physical/Chemical Characteristics

Hazard Storage Compatibility Code	NR
NRC Licence Number	NR
Net Propellant Weight (Ammo)	NR
Appearance/Odor	Black Liquid
Boiling Point	170 DEG C
Melting Point	NR
Vapor Pressure	NR
Vapor Density	NR
Specific Gravity	1.1
Decomposition Temperature	NR
Evaporation Rate	NR
Solubility in Water	<2
Percent Volatiles by Volume	<16
Chemical pH	NR
Corrosion Rate	NR
Container Pressure Code	4
Temperature Code	8
Product State Code	U

SECTION IV - Fire and Explosion Hazard Data

Flash Point Flash Point Method Lower Explosion Limit	163 C UNK NR
Upper Explosion Limit	NR
Extinguishing Media	USE WATER FOG, CARBON DIOXIDE, DRY CHEMICAL OR FOAM
Special Fire Fighting Procedures	WEAR FULL FIRE FIGHTING PROTECTIVE CLOTHING AND SELF CONTAINED BREATHING APPARATUS. MATERIAL NEAR FIRE SHOULD BE COOLED WITH WATER SPARY OR FOG. CAUTION WHEN US
Unusual Fire/Explosion Hazards	THERMAL DECOMPOSITION OR COMBUSTION MAY PRODUCE DENSE SMOKE, OXIDES OF CARBON, AS WELL AS LOW MOLECULAR WEIGHT ORGANIC COMPOUNDS WHOSE COMPOSITIONS HAVE NOT BEEN IDENTIFIED

SECTION V - Reactivity Data

Stability	YES
Stability Conditions to Avoid	HIGH TEMPERATURES
Materials to Avoid	AVOID CONTACT WITH STRONG OXIDIZING AND REDUCING AGENTS AND STRONG ACIDS AND BASES
Hazardous Decomposition Products	SMOKE, OXIDES OF CARBON, LOW MOLECULAR WEIGHT ORGANIC COMPOUNDS WHOSE COMPOSITIONS HAVE NOT BEEN CHARACTERISED
Polymerization Conditions to Avoid	HEXAMTHYLENETETRAMINE REACTS VIOLENTLY WITH NA202

SECTION VI - Health Hazard Data

Route of Entry: Skin Route of Entry: Ingestion Route of Entry: Inhalation Health Hazards - Acute and Chronic	YES YES ILQUID FURFURYL ALCOHOL AND HIGH CONCENTRATIONS OF VAPOURS MAY BE HIGHLY IRRITATING TO THE EYES, SKIN, MUCOUS MEMBRANES AND RESPIRATORY TRACT. INGESTION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, CRAMPING AND VOMITING. EXPOSURE TO HIGH CONCENTRA- TIONS OF VAPOURS MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, DISORIENTATION, FA
Symptoms of Overexposure	IRRITATING TO THE EYES, SKIN, MUCOUS MEMBRANES, RESPIRATORY TRACT. DERMATITIS. COUGH, SHORTNESS OF BREATH AND DECREASE IN PULMONARY FUNCTION
Medical Conditions Aggravated by Exposure	PRE-EXISTING PULMONARY, DERMAL, KIDNEY, AND LIVER DISORDERS MAY POSSIBLY BE AGGRAVATED BY PROLONGED EXPOSURE TO HIGH CONCENTRATIONS OF THE MATERIALS
Emergency/First Aid Procedures	INHALE: REMOVE TO FRESH AIR, SEEK MEDICAL ATTENTION. EYES: FLUSH WITH WATER FOR 15 MIN. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS. SKIN: WASH THE AFFECTED AREA WITH MILD SOAP AND WATER. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS. INGEST: GIVE TWO GLASSES OF WATER TO DILUTE AND INDUCE VOMITING

SECTION VII - Precautions for Safe Handling and Use

Steps if Material Released/Spilled	ELIMINATE ALL IGNITION SOURCES, ISOLATE SPILL, EVACUATE PERSONNEL. PUMP INTO CONTAINERS. ABSORB RESIDUE WITH CLAY, SAND OR OTHER SUITABLE MATERIAL. DO NOT ALLOW MATERIAL OR RINSE WATER TO ENTER STORM OR SANITARY SEWERS
Waste Disposal Method	IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULA- TIONS
Handling and Storage Precautions	STORE IN LABELLED, CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION. DO NOT STORE WITH OR NEAR INCOMPATIBLE CHEMICALS

Other Precautions

CARBON AND GRAPHITE DUSTS ARE ELECTRICALLY CONDUCTIVE. ACCUMULATIONS OF DUSTS MAY CAUSE SHORTING OF ELECTRICAL CIRCUITS. CARE SHOULD BE TAKEN TO SEAL ELECTRICAL CIRCUITS AND SWITCHES THAT MAY BE AFFECTED. INCLUDES OUTSIDE ELECTRICAL EQUIPMENT

SECTION VIII - Control Measures

Respiratory Protection	1/2 FACE RESPIRATOR WITH ORGANIC VAPORS AND PARTICULATE CARTRIDGES
Ventilation	LOCAL EXHAUST
Protective Gloves	BUTYL RUBBER GLOVES
Eye Protection	CHEMICAL SPLASH GOGGLES
Other Protective Equipment	WHERE NORMAL WORK CLOTHES MAY BECOME CONTAMINATED BY PRODUCT, PROTECTIVE BUTYL RUBBER COATED COVERALLS ARE RECOMMENDED
Work Hygenic Practices	THOROUGHLY WASH ANY CONTAMINATED CLOTHING BEFORE REUSE
Disposal Code	0

SECTION IX - Label Data

Protect Eye	YES
Protect Skin	YES
Protect Respiratory	YES
Chronic Indicator	UNKNOWN
Contact Code	UNKNOWN
Fire Code	UNKNOWN
Health Code	UNKNOWN
React Code	UNKNOWN

SECTION X - Transportation Data

Container Quantity	15
Unit of Measure	LB

SECTION XI - Site Specific/Reporting Information

Volatile Organic Compounds (P/G)	0
Volatile Organic Compounds (G/L)	0

SECTION XII - Ingredients/Identity Information

Ingredient #	01
Ingredient Name	1,3,5,7-TETRAAZATRICYCLO[3.3.1.13,7]DECANE
CAS Number	100970
Proprietary	NO
Ingredient #	02
Ingredient Name	(POWDER) CARBON
CAS Number	7440440
Proprietary	NO
Ingredient #	03
Ingredient Name	(POWDER) PHENOLIC RESIN
CAS Number	9403354
Proprietary	NO
Ingredient #	04
Ingredient Name	(POWDER) TRANSIL OIL
CAS Number	64742456
Proprietary	NO
Ingredient #	05
Ingredient Name	(POWDER) HEXAMETHYLENETETRAMINE
CAS Number	108970
Proprietary	NO